

TITLE: CONFIGURABLE TRANSFORMATION OF ELECTRONIC DOCUMENTS

APPLICANT: ADAM L. BERGER, RICHARD D. ROMERO, GREGORY C. SCHOHN AND CLARK W. SLATER

Victor Mahoney
Typed or Printed Name of Person Signing Certificate

5

10

15

20

25

Automatic content transformation systems convert electronic documents originally designed for transmission to and rendering on large-screen devices into versions suitable for transmission to and rendering on small-display, less powerful devices such as mobile phones. See, for example, Wei-Ying Ma, Ilja Bedner, Grace Chang, Allan Kuchinsky, and HongJiang Zhang. *A Framework for Adaptive Content Delivery in Heterogeneous Network Environments. of SPIE Multimedia Computing and Networking 2000*. San Jose, CA, January, 2000.

10 SUMMARY

In general, in one aspect, the invention features a method that includes altering portions of a text of an original version of a digital document to produce a revised version of the digital document in which the text is shorter than the text of the original document, receiving over a communication channel a request for the digital document from a device connected to the channel, and transmitting the revised version over the communication channel in response to the request.

Implementations of the invention include one or more of the following features. The altering includes reducing the size of an image included in the original document, for example, by image compression, resampling, or conversion from color to black-and-white. The altering of portions of the text includes applying more than one transformation selectively to the text. Transformations to be applied to the text as part of the altering step are selected based

Attorney Docket 12481-002P01

Attorney Docket 12481-002P01

with different client devices with respect to preferred alterations to be performed on full web pages requested by client devices that are not configured to display full web pages, the alterations making the documents more suitable for display on the client devices.

- 5 In general, in another aspect, the invention features a method that includes obtaining from a client device information about preferences with respect to preferred alterations to be performed on full documents requested by a client device that is not configured to display the full documents, and associating the preferences with
10 the client device in a database.

In general, in another aspect, the invention features a method that includes creating content for web pages to be served to types of client devices that are not configured to display full web pages, and storing information about transformations that are to be made to the full web pages to make them suitable for display on the client devices. The stored information associating each of the types of devices with transformations to be made to full web pages requested by that type of device.

Other advantages and features will become apparent from the
20 following description, and from the claims.

DESCRIPTION

(Figure 1 shows a document transforming and serving system.

Figure 2 shows a document.

of the original document—text blocks, images, and so on. Internal nodes 44 of the tree represent structural and markup information—markers denoting paragraphs, tables, hyperlinked text, regions of bold text, and so on. One strategy for accomplishing the segmentation task is to use an agglomerative, bottom-up leaf-clustering algorithm. The leaf-clustering approach begins by placing each leaf in its own segment (as shown in figure 4) and then iteratively merging segments until there exists no adjacent pair of segments that should be merged. Figure 5 shows the same tree after two merges have occurred, leaving merged segments 50, 52.

Each merging operation generates a new, modified tree, with one fewer segments. Each step considers all adjacent pairs of segments, and merges the pair that is optimal according to a scoring function defined on candidate merges. An example scoring function is described below. When the algorithm terminates, the final segments represent partitions of the original XML tree.

SCORING FUNCTION

In one example scoring function, a lower score represents a more desirable merge. (In this context, one can think of “score” of a merge as the cost of performing the merge.) In this example, the score of merging segments x and y is related to the following quantities:

2. The familial proximity of the segments: All else being equal, if segments x and y have a common parent z , then they comprise a more desirable merge than if they are related only through a grandparent (or more remote ancestor) node. That two segments are related only through a distant ancestor is less compelling evidence that the segments belong together than if they are related through a less distant ancestor.

3. The node replication required by the merge: Internal nodes may have to be replicated when converting segments into well-formed documents. Of course, in partitioning an original document into subdocuments, one would like to minimize redundancy in the resulting subdocuments.

Defining by $d(x,y)$ the least number of nodes one must travel through the tree from segment x to segment y , and by $r(x,y)$ the amount of node replication required by merging segments x and y . A general candidate scoring function is then

$$\text{score}(x,y) = A(|x|+|y|) + B(dx,y) + C(rx,y),$$

Figure 1 consists of 12 histograms arranged in a single column. Each histogram represents the frequency distribution of the number of non-zero elements in a vector x for a specific value of n . The x-axis for all histograms is 'Number of non-zero elements in x ' with major ticks at 0, 20, 40, 60, 80, 100, and 120. The y-axis is 'Frequency' with major ticks at 0, 2, 4, 6, 8, and 10. The histograms are labeled with n values: 10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, and 120. As n increases, the distribution of non-zero elements becomes more concentrated around a central value, which appears to be approximately 60-70.

addressed, for instance, by automatic computer programs such as
the one described in M. Hearst, *TextTiling: Segmenting text into
multi-paragraph subtopic passages*. Computational Linguistics
23(1) 33-65, 1997. TextTiling is an algorithm designed to find
5 optimal locations to place dividers within text sources.

Returning to figure 3, the next step is to convert the segments of
the final tree into individual, well-formed XML documents (36).
Doing so may require replication of nodes. For instance, in Figure
5, merging leaves B and F has the effect of separating the siblings
10 F and G. This means that when converting the first and second
segments of the tree on the right into well-formed documents, each
document must contain an instance of node C. In other words,
node C is duplicated in the set of resulting subdocuments. The
duplication disadvantage would have been more severe if nodes F
15 and G were related not by a common parent, but by a common
grandparent, because then both the parent and grandparent nodes
would have to be replicated in both segments.

After having computed a segmentation for the source document,
the proxy server stores the individual subdocuments in a cache or
20 database (38) to expedite future interaction with the user. When the
user follows a hyperlink on the first subdocument to access the
next subdocument in the sequence, the request is forwarded to the
proxy server, which responds (39) with the appropriate
subdocument, now stored in its cache.

Attorney Docket 12481-002P01

User	State
12345	[subdoc 1] [subdoc 2] [subdoc 3] ... [subdoc 8]
45557	[subdoc 1] [subdoc 2]
98132	[subdoc 1] [subdoc 2] [subdoc 3] ... [subdoc 6]

Many client devices cannot process documents written in XML and can process only documents written in another markup language, such as text, HTML, WML or HDML. Translation of the XML subdocuments to the other format (43) could be done at the proxy server by any available translator.

The agglomerative segmentation algorithm (Algorithm 1, above) is performed only once per source document, at the time the user first

- 5 Once the segmentation of a document into subdocuments has been achieved, it is possible to use the subdocuments in a variety of ways other than simply serving them in the order in which they appear in the original document.

For example, as shown in figure 17, an original HTLM document 100 may contain a form 102. In order to make the user's interaction with the page sensible, it may be useful to separate the form from the rest of the page and replace it with a link in one of the subdocuments. Then the user can invoke the link on his local device to have the form presented to him. If he prefers not to see or use the form, he can proceed to navigate through the other subdocuments as discussed earlier without ever getting the form.

For this purpose, the document can be segmented into subdocuments 104, 106, and 108 that represent parts of the main body of the document and subdocuments 110, 112 that represent portions of the form 102. One of the subdocuments 106 contains an icon 114 that represents a link 116 to the form. Other links 118, 120, and 122 permit navigation among the subdocuments as described earlier.

TRANSFORMATION

- The content of the subdocuments that are served to the user devices can be automatically transformed in ways that reduce the amount of data that must be communicated and displayed without rendering the information represented by the data unusable. Users can customize this automatic transformation of electronic documents by expressing their preferences about desired results of the transformation. Their preferences are stored for later use in automatic customized transformation of requested documents.
- 10 For example, a user may wish to have words in original documents abbreviated when viewing the documents on a size-constrained display. Other users may find the abbreviation of words distracting and may be willing to accept the longer documents that result when abbreviations are not used. These preferences can be
- 15 expressed and stored and then used to control the later transformation of actual documents.

We discuss steps in transforming the documents first and then the process of soliciting user preferences.

TRANSFORMING DOCUMENTS

- 20 As shown in figures 1 and 6, and as explained earlier, when the user 6 of the device 10 requests (11) the document 12 (e.g., by entering a URL into a browser running on the device, selecting from a bookmark already stored in the browser, or selecting a link

Attorney Docket 12481-002P01

from a hypertext document previously loaded into the browser), the proxy server receives the request (18) and fetches (20) the document from the origin server.

After receiving the document from the origin server, the proxy
5 computer consults (24) a database 26 of client preferences to determine the appropriate parameters for the transformation process for the device 8 for the user who is making the request. The proxy computer then applies (28) the transformations to the document to tailor it for transmission to (30) and rendering (32) on
10 the client device.

The HTTP header in which the client device advertises information to the proxy server about itself can include two relevant pieces of information:

1. A unique identifier for the device: For example, for
15 wireless Internet devices equipped with a microbrowser distributed by Phone.com, the HTTP header variable X-UP-SUBNO is bound to a unique identifier for the device.
2. The device type: For example, the HTTP header variable
20 USER-AGENT is bound to a string that describes the type of browser software installed on the device.

When document transformation occurs, the proxy computer has already obtained the unique ID and can use it as a key to look up, in the database, a set of preferences associated with the user.

Attorney Docket 12481-002P01

Figure 7 shows an example of rows in a fictitious database 24. Each row 40 identifies a device by the device's telephone number. The row associates user preferences (four different ones in the case of figure 7) with the identified device. In this case, the telephone
5 number (e.g., of a mobile phone) is the unique ID that serves as the key for the records in the database.

Having consulted the database to determine the appropriate preference values for this user, the proxy computer can use these values to guide its transformation process. Thus, as shown in
10 figures 1 and 4, the inputs to the transformation process are a source document (in HTML, for instance) and a set of user preference values (one row in the database from figure 6)

As shown in figure 8, document transformation includes a sequence of operations, such as date compression 52, word
15 abbreviation 54, and image suppression 55, in converting an original document to a form more suitable for rendering on a small-display device. At every step, the preferences for the target device are used to configure the transformation operations. For instance, the client-specific preferences could indicate that word
20 abbreviation should be suppressed, or that image suppression 55 should only be applied to images exceeding a specified size.

In addition to being suppressed, images can be subjected to other kinds of transformations to reduce their size. For example, images may be compressed, downsampled, or converted from color to
25 black and white.

Attorney Docket 12481-002P01

Examples of user-configurable parameters include the following:

Abbreviations

To reduce the space required to display a document, words may be abbreviated. There are many strategies for compressing words, such as truncating long words, abbreviating common suffices (“national” becomes “nat’l”), removing vowels or using a somewhat more sophisticated procedure like the Soundex algorithm (Margaret K. Odell and Robert C. Russell, United States Patents 1,261,167 (1918) and 1,435,663 (1922)). The corresponding user-configurable parameter would be a Boolean value indicating whether the user wishes to enable or disable abbreviations. Enabling abbreviations reduces the length of the resulting document, but may also obfuscate the meaning of the document.

Suppression of images

Many small-screen mobile devices are incapable of rendering bitmapped images. Even when possible, rendering of large images may require lengthy transmission times. Bitmapped images are likely to degrade in quality when rendered on low-resolution screens. For these reasons, users may control whether and which kinds of bitmapped images are rendered on their devices. The corresponding user-configurable parameter in this case could be, for instance, a Boolean value (render or do not render) or a maximum acceptable size in pixels for the source image.

Attorney Docket 12481-002P01

5

10

15

SPECIFYING AND STORING PER-DEVICE PREFERENCES

20

Entering preferences from the small-display device

A user can enter and maintain preferences by visiting the proxy computer using the same small-display device he uses for Internet access. As shown in figure 9, the proxy computer could store a hypertext form 60 that users of small-display devices retrieve and fill in according to their preferences. Upon receiving an HTTP request 62 from a client device, the proxy computer will automatically (using the HTTP protocol) obtain the unique identifier for the client device. The proxy computer then transmits to the user a form 64 that contains a set of preferences. If the client device already has an associated entry in the database, the current value for each parameter can be displayed in the form; otherwise, a default value will be displayed. The user may change parameters on this form as he sees fit and then submit the form back 66 to the proxy computer, which stores the updated values in the database in the record associated with that client device.

Entering preferences from a conventional computer

Alternatively, the user can visit the same URL using a conventional web browser on a desktop or laptop computer. The proxy computer will be unable to determine automatically from the HTTP header information which device to associate the preferences with. The user must explicitly specify the unique identifier—phone number, for instance—of the device for which the user wishes to set the preferences.

In the previous discussion, the user is a person accessing a remotely-stored document using a small-screen device, and a proxy computer (which performs the transformations) mediates between the user's device and the Internet as a whole.

The origin server may also offer to an author of content an ability to configure transformations once for any user retrieving documents from that server for a particular type of client device. In other words, instead of offering the end user the ability to customize the transformations, one can instead offer this ability to the person or institution that authored the content. This scenario is

20

relevant when the content provider desires strict control over the appearance of their content on small-display devices.

Rather than storing a database of user (individual device) preferences, then, the origin server stores only a single set of parameter values for the transformation for each type of device. The information flow from user to origin server is thus:

1. User requests a document from origin server.
2. Origin server receives the request and information on the type of client device making the request.
- 10 3. Origin server consults the transformation parameters appropriate for that device in processing the requested document.
4. Origin server delivers the transformed document to the client device.

15 An example of the entries in the database that are used for step 3 is shown below:

Device type	Word abbreviations?	Images?	Max. doc size	Date abbrevs?
Samsung SCH-8500	yes	no	2000 bytes	yes
Motorola StarTAC	no	yes	16000 bytes	yes
Palm VII	no	no	1492 bytes	no

412-309-8882	yes	yes	1223 bytes	no
--------------	-----	-----	------------	----

The previous section described a method for end users to specify and store preferences, to be associated with a single device. This section described a method for content creators to configure the transformation of documents delivered from their origin server. These two scenarios are not incompatible. Imagine that an end user requests a document X from an origin server Y. Imagine further that the end user has registered a set of preferences for his transformations, and that there exists on the origin server a separate set of preferences for documents delivered from that origin server. The document will be transformed first according to the preferences in the origin server, and then according to the end user's preferences. In this scenario, the end user's preferences sometimes cannot be honored. For instance, if the end user does not want words abbreviated, but the preferences for the origin server specify that words are to be abbreviated, then the end user will receive, despite his preferences, a document containing abbreviated words.

STORING PREFERENCES ON THE CLIENT DEVICE

20 An alternative strategy for associating preferences with devices is to use the HTTP “cookie” state mechanism (D. Kristol and L. Montulli. RFC 2109: HTTP State Management Mechanism. (1997). <http://www.w3.org/Protocols/rfc2109/rfc2109.txt>). In

Attorney Docket 12481-002P01

- 5 1. A user of a small-display device submits a request to the proxy computer for the preferences form document. The form document is transmitted from the proxy computer to the device.
2. The user fills in his preferences and submits the filled-in form back to the proxy computer.
- 10 3. The proxy computer responds with a confirmation document and also transmits, in the HTTP header information to the client device, a cookie containing that user's preferences. For example, the cookie might look like

Set-Cookie: PREFS="abbrevs:yes images:no dates:yes ...";
15 path=/; expires=04-Sep-01 23:12:40 GMT
4. The client device stores this cookie as persistent state.
5. When a user of the client device subsequently requests a document from the proxy computer, the device also transmits to the proxy computer the cookie containing the stored preferences:
- 20 Cookie: PREFS="abbrevs:yes images:no dates:yes ...";
6. Equipped with the preferences for this client, the proxy computer applies these preferences in transforming the requested

Attorney Docket 12481-002P01

The content transformation system intercepts requests from non-traditional client devices, customizes the requested documents for display on the target device 78, and transmits the transformed documents 74 to the client. The content transformation system employs user preferences 76 and device specifications 64 to guide the document transformation process.

If the requested page 72 has been designed specifically for the client device making the request, content transformation isn't necessary. But designing documents for wireless devices is no simple matter. The document must be written in the markup language accepted by the device—sometimes HTML, but more often another markup language such as WML, HDML, or a proprietary language. Because the hundreds of different wireless data devices each have different capabilities 64 , a content creator faces the prospect of creating a separate version not only for each target markup language, but for every possible target device. The content provider also needs to understand how to detect the type of client device and create a document optimally formatted for that client.

By using system 70, which automatically compresses and reformats a document 72 for optimal display on a specific target device, content creators are free to concentrate on their core competency--writing content--and not on retargeting content for a

Attorney Docket 12481-002P01

- 5 Content transformation systems can use automatic document
segmentation to stage the delivery of large documents to devices
incapable of processing large documents in their entirety.

The core content transformation component 81 can include the segmentation process described earlier. The XML cache object 84

- 10 is where the per-user subdocuments are stored for the segmentation
process.

Content transformation is a server-side technology and can naturally be deployed at various locations in the client-origin server channel, anywhere from the wireless gateway to the origin server that holds the original content. The following table lists a few of the places content transformation is applicable.

Setting	Explanation	Benefits
Within a web server	As a plug-in module to Apache and competing web server software, allowing on-the-fly customized transformations to handheld devices.	After installation, the web server can automatically detect requests from wireless clients and generate content optimized for the requesting device.
Within a reverse proxy server	Transform all content from a single site or group of sites at a centralized location.	Same as above, but also exploits the proxy cache to centralize the transformation process and reduce server load.
Within a proxy server	A resource shared by a community (a company, for instance)	Enables users of the proxy to access the entire Internet with their wireless device.

Attorney Docket 12481-002P01

	instance)	with their wireless device.
At the wireless gateway	The gateway processes HTTP requests from wireless clients by fetching the requested URL and passing the document through the transformation process before delivering the document to the client device.	Allows all subscribers to that wireless service to access the entire Internet, customized to their device.
As standalone software	Integrated as part of the web-development process. Web developers can use the software as a rapid prototyping tool, refining the output by hand if desired.	Allows companies to create custom wireless content at a fraction of the cost associated with creating the content entirely by hand.

Figure 14 shows an example input document (a full-size web page) that was divided into five subdocuments. Figure 15 shows the bottom of the fourth subdocument 72, corresponding to the middle of the “Bronx-Whitestone Bridge” section of the original page. The hyperlinks (icons) labeled “prev” 74 and “next” 76 bring a user to the third and fifth subdocuments, respectively, when invoked. Figure 16 shows the beginning of the fifth subdocument 78, which begins where the fourth leaves off.. The user can scroll through the subdocument as needed. In some implementations, as shown, the icons 74, 76 are only displayed when the user has scrolled to the beginning or end of the subdocument. In other examples, the icons could be displayed at all times.

15 In figures 15 and 16, the numbers and words in the original have been abbreviated (“one” became “1”, “and” became “&”) and days of the week have been shortened.

